

SPECIFICATIONS

# 8300 series

## Light Industrial Mobile Computer



		8300	8330	8360	8370
<b>Communication</b>	Options	Batch	Bluetooth+Wi-Fi	Bluetooth	Wi-Fi
	Specifications	Infrared	BT Class 2+802.11b/g	BT Class 1	802.11b/g
	Coverage (line of sight)	Typically 30 cm / 12 in.	BT-10 m/32.8 ft, WiFi 350 m/1148 ft	250 m / 820 ft.	350 m/1148 ft
<b>Power</b>	Operating power	Li-ion 3.7 V/ 1800mAh battery			
	Working hour (laser scan/5 sec)	270 hours	40 hours	40 hours	40 hours
	Backup power	3.0V, 7.0mAh, rechargeable Lithium battery			
	Data retention	36 days			
<b>General Characteristics</b>	Computing	16 bit CMOS CPU, 2MB flash memory; 2MB SRAM (additional 4MB/8MB options are available)			
	Display	LCD 128x64 with LED backlight			
	LED	Green and red dual color			
	Keypad	24 Numeric or 39 Alphanumeric rubber keys with LED backlight			
	Alerts	Programmable, 1KHz or 4KHz Buzzer; Vibrator			
	Dimensions (L x W x H)	170mm x 77mm x 47mm / 6.7in x 3in x 1.9in			
	Weight (batch type, laser reader)	290g / 10.2oz			
<b>Scanners</b>	Reader options	Linear imager, Laser, Long range laser			
	Light source	Linear imager: 650nm Red LED; Laser: Visible Laser Diode			
	Scan rate	Linear imager: 100/sec; Laser: 100/sec; Long range laser: 35/sec			
	Scan angle	Laser: 47 degree; Long range laser: 42 degree			
	Reading range	Linear image : 5~29.5cm/0.16ft ~0.96ft; Laser: 1~45cm / 0.03ft~1.47ft; Long range laser: 5~218cm / 0.16ft~715ft (depends on barcode resolution)			
<b>RFID</b>	Frequency 13.56 MHz	Optional	-	-	Optional
	Supported standard list	Mifare ISO 14443B, ISO 15693, ICODE			
<b>Environmental</b>	Operating temperature	-10°C to 60°C / 14°F to 140°F			
	Storage temperature	-20°C to 70°C / -4°F to 158°F			
	Humidity	Operating: Non-condensed 10% to 90%, Storage Non-condensed: 5% to 95%			
	Impact resistance	1.2M / 4 ft (5 drops per 6 sides) / IP65			
	Electrostatic discharge	± 15 kV air discharge, ± 8 kV direct discharge			
	EMC regulation	FCC, CE, C-Tick			
<b>Programming Language</b>	C, BASIC, and a Windows-based applications generator				
<b>Accessories</b>	Charging & communication cradle (RS-232 cable, Keyboard wedge cable, USB cable), Modem cradle (56K), Ethernet cradle (10/100 BaseT), 4-slot battery charger				
<b>Warranty</b>	1 year				

## ACCESSORIES



Charging & Communication Cradle



Modem Cradle Ethernet Cradle



4-slot Battery Charger



©2006 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc., and any use of such marks by CipherLab is under license.



**HEADQUARTERS**  
**CipherLab Co., Ltd.**  
 12F, 333 Dunhua S. Rd., Sec. 2  
 Taipei, Taiwan 106  
 Tel +886 2 8647 1166  
 Fax +886 2 8732 2255  
 www.cipherlab.com

**CipherLab China**  
 Suite 1306, 1065A, Jaojiabang Rd.  
 Xuhui District, Shanghai,  
 China 200031  
 Tel +86 21 3368 0288  
 Fax +86 21 3368 0286

**CipherLab USA**  
 2552 Summit Avenue  
 Plano, Texas USA 75074  
 Tel +1 469 241 97799  
 Toll Free 888 300 9779  
 Fax +1 469 241 0697

**CipherLab EMEA**  
 Airedale House  
 Clayton Wood Rise  
 Leeds, LS16 6RF, UK  
 Tel +44 113 274 7823  
 Fax +44 113 274 7822