

Sensor Tag T34



- Multi-sensor combinations
- User-programmable ID code or data
- Safe to mount directly on a metal surface
- Unaffected by surrounding structures
- Robust in drop, shock and vibration
- No battery run-out or disposal concern

Typical Performance

Sensor – switch status	16 combinations	
Memory size	16 bytes	
Transmission rate	10 messages per sec	
	Reading distance	Passage speed
R10	2 m	1 m/s
R11 / R12	1.5 m	0.5 m/s
R15 / R16	2 m	0.8 m/s
R60	20 cm	-

Details about reading/writing distance, passage speed, tag orientation and more can be found in Technical Manual.

Technical Data

Dimensions	178 x 26 x 10 mm
Cable length	2 m
Weight	20 g
Temperature	-20 to +70 °C (operating)
Temperature	-40 to +85 °C (storage)
Humidity (IEC 60068)	95%, non-condensing
Protection class (IEC 60529)	IP 68
Bump (IEC 68-2-29)	1000x 10g 6ms x 3 dir
Drop (IEC 68-2-32)	10x 1m on concrete
Vibration (IEC 68-2-29)	0.02 g ² /Hz, 0.5h x3 dir, 10-2000 Hz
Immunity (EN 61000-6-2)	10/3 V/m, 4/8 kV ESD, 1kV transient
Emission (EN 61000-6-3)	30/37 dBuV/m @ 10m
Mounting	Screw or pad mounting
Cover	Polycarbonate
Label	Type code, regulatory marking, serial number

Ordering codes

Sensor Tag	T34
------------	-----

DST34B

In a continuing effort to improve our products, Scirocco AB reserves the right to change specifications and features without prior notice.